


- NOTE:
- ① WIRE IS NOT USED WHEN EXTERNAL INTERLOCK SWITCH OR STOP BUTTON IS USED.
  - ② OBSTRUCTION SENSING DEVICES MAY BE N.O. TYPE (STANDARD AIR SWITCH, ELECTRIC EDGE, ETC.) OR N.C. "FAILSAFE" TYPE (PHOTOCCELL, ETC.).
  - ③ #1 DIPSWITCH MUST BE SET TO "OFF".



PROGRAM SWITCHES  
 RUN TIME SAFETY SELECT \*3\*  
 RUN TIME SAFETY SELECT \*2\*  
 CLOSE SAFETY SELECT \*1\*

RUN TIME SAFETY SELECT:  
 28.8 SECONDS: SWITCHES 2 & 3 \*ON\*.  
 45 SECONDS: SWITCH 2 \*OFF\*, SWITCH 3 \*ON\*.  
 60 SECONDS: SWITCHES 2 & 3 \*OFF\*.  
 90.13 SECONDS: SWITCH 2 \*ON\*, SWITCH 3 \*OFF\*.

WIRED FOR:  
 115V-1 $\phi$

MODEL:	MSW GATE OPERATOR
	FAL55E2PSCB5 MOTOR CONTROL
DATE:	2-94 REV: 6
BY:	R.L. Dr. by: J.D.
SPECIAL:	w/0 3 HARDW LOOP MOD.
	PSC MOTOR
WIRING DIAGRAM	5535