



- NOTES:
- 1- WIRE-NOT FURNISHED WHEN EXTERNAL INT'LK SWITCH IS USED. - NOT FURNISHED WHEN STOP BUTTON IS USED.
 - 2- WIRE-NOT FURNISHED WHEN TIMER DEFEAT SWITCH IS USED
 - 3- FOR MOMENTARY CLOSE MOVE RED WIRE TO TERMINAL #5.
 - A- TREADLES, PULL SWITCHES, KEY SWITCHES, PHOTO-ELECTRIC DEVICES, ECT. MAY BE CONNECTED TO TERMINALS INDICATED
 - B- REMOTE CONTROL UNITS (EXCLUDING TREADLES AND PHOTO-ELECTRIC UNITS). PULL SWITCHES AND SINGLE CONTACT CONTROL STATIONS, MAY BE CONNECTED TO TERMINALS INDICATED.

PowerMaster	
WIRING TYPE: SAFETY EDGE TO REVERSE WITH OPTIONAL TIMER	
MTR/CNTR: 3 Ø	DATE: 1-20-97
BY: F.S.	REV. 10
SPECIAL: OPTIONAL TIMER CIRCUIT IN DASHED LINES.	
WIRING DIAGRAM NO. 1333-2	
© Copyright PowerMaster 1997	
No portion of this diagram may be reproduced without the expressed written permission of the manufacturer.	