



FOR MOMENTARY PRESSURE CLOSE, MOVE THIS RED WIRE TO TERMINAL # 5

ALL CONTROL WIRING IS 115V

- NOTES:
- 1- WIRE-NOT FURNISHED WHEN EXTERNAL INT'LK SWITCH IS USED.
 - 2- WIRE-NOT FURNISHED WHEN STOP BUTTON IS USED.
 - 3- WIRE-NOT FURNISHED WHEN TIMER DEFEAT SWITCH IS USE.
 - A-TREADLES,PULL SWITCHES, KEY SWITCHES, PHOTO-ELECTRIC DEVICES, ECT. MAY BE CONNECTED TO TERMINALS INDICATED
 - B-REMOTE CONTROL UNITS (EXCLUDING TREADLES AND PHOTO-ELECTRIC UNITS). PULL SWITCHES AND SINGLE CONTACT CONTROL STATIONS, MAY BE CONNECTED TO TERMINALS INDICATED.

OBSTRUCTION SENSING DEVICE (24V)
(KEEP SEPARATE FROM ALL OTHER WIRING)

PowerMaster	
WIRING TYPE: SAFETY EDGE TO REVERSE WITH OPTIONAL TIMER	
MTR/CNTR: 3 Ø	REV. 0
DATE: 3-5-99	BY: F.S.
SPECIAL: 115 VAC CONTROL 24V S.E.	
WIRING DIAGRAM NO. 333-A1PD	
© Copyright PowerMaster 1997 No portion of this diagram may be reproduced without the expressed written permission of the manufacturer.	