



- NOTES:
- 1- WIRE-NOT FURNISHED WHEN EXTERNAL INT'LK SWITCH IS USED. - NOT FURNISHED WHEN STOP BUTTON IS USED.
  - 2- WIRE-NOT FURNISHED WHEN TIMER DEFEAT SWITCH IS USE.
  - 3- FOR MOMENTARY CLOSE. MOVE RED WIRE TO TERMINAL #5.
  - A- TREADLES, PULL SWITCHES, KEY SWITCHES, PHOTO-ELECTRIC DEVICES, ECT. MAY BE CONNECTED TO TERMINALS INDICATED
  - B- REMOTE CONTROL UNITS (EXCLUDING TREADLES AND PHOTO-ELECTRIC UNITS). PULL SWITCHES AND SINGLE CONTACT CONTROL STATIONS, MAY BE CONNECTED TO TERMINALS INDICATED.

<b>PowerMaster</b>	
WIRING TYPE: SAFETY EDGE TO REVERSE WITH: OPTIONAL TIMER	
MTR/CNTR: 1 Ø	REV: 9
DATE: 11-22-88	BY: F.S.
SPECIAL: OPTIONAL TIMER CIRCUIT IN DASHED LINES.	
WIRING DIAGRAM NO. 331-2	
© Copyright PowerMaster 1987 No portion of this diagram may be reproduced without the expressed written permission of the manufacturer.	