



**NOTES:**

1. WIRE IS NOT USED WHEN EXTERNAL INTERLOCK SWITCH OR STOP BUTTON IS USED.
2. EXT'L INT'CK WHEN REQ. ALL INTERLOCKS WIRE IN SERIES BETWEEN TERMINAL NO. 4' AND STOP BUTTON.
3. TREADLES, PULL SWITCHES, KEY SWITCHES, WANDS, PHOTO-ELECTRIC DEVICES, ETC. MAY BE CONNECTED TO TERMINALS INDICATED.
4. TIMER DEFEAT SWITCH, WHEN USED, WILL DISABLE TIMER AND UNLESS FULLY CLOSED WILL MAINTAIN GATE IN OPEN POSITION.
5. MAXIMUM RUN TIMER SEE OPPOSITE SIDE OF SHEET.
6. SINGLE CONTACT CONTROLS SUCH AS PULL SWITCHES AND ONE BUTTON STATION MAY BE CONNECTED TO TERMINALS 1 & 2.
7. TERMINALS NO. 3 & NO. 4 PROVIDE 24 VAC FOR ACCESSORIES.

WARNING: DO NOT SHORT TERMINALS 3 & 4 TOGETHER!

FOR:	VAC-15
COMMERCIAL SLIDE GATE	FOR
REV: N	BM.
OPTIONAL: TIMER TO CL IN DASHED LINE	
WIRING DIAGRAM NO. 331-LR-MRT-2	
FOR MODEL SGI, SG, BSG, SINGLE, MASTER/S�AVE	