



- NOTES:**
1. ALL CONTROLS ARE N. O. DEVICES
 2. DIODES REQ. FOR 3 BS CONTROL
 3. INTERLOCK SWITCH WHEN REQ.
 4. DRY CAPACITOR 70 MFD 220 VAC
 5. CONNECT Y & BK WIRES TOGETHER WHEN INTERLOCK SWITCH IS NOT USED.
 6. FOR MOMENTARY PRESS. MOVE OR/BL WIRE TO TERM. 7 FROM RELAY "R1" AND REMOVE "OR" WIRE BETWEEN TERM. 5 AND RELAY "R1". AN OBSTRUCTION SENSING DEVICE MUST BE CONNECTED TO TERM. 8 & 9.
 7. N. O. STOP BUTTON REQ.
 8. RADIO CONTROL MUST USE MOMENTARY PRESS. WIRING (NOTE NO 6). THIS IS TYPICAL FOR ALL SINGLE CONTACT CONTROLS.

MODEL LH - LJ - LT (CONST. PRESS. DOWN)	
W / 411R CONTROL BOARD	
REV: 6	BM. 7 - 14 - 95
SPECIAL: WIRED TO ACCEPT RADIO CONTROL, ONE BUTTON STATION, KEYSWITCH, THREE BUTTON STATION, AND SENSING DEVICE.	
WIRING DIAGRAM	LD - 331R - CPD