



<b>PowerMaster</b>	
MODEL: SJ	PRB-2 MOTOR CONTROL
DATE: 3/7/00	REV. 1
BY: F.S.	R.P.L.
SPECIAL: PSC MOTOR	
WIRING DIAGRAM SJ-345	
© Copyright PowerMaster 1997 No portion of this diagram may be reproduced without the express written permission of the manufacturer.	

- ② RADIO RCVR
- ①A ONE BUTTON OPEN/CLOSE
- ②A OPEN ONLY
- ③ 2 WIRE EDGE "CLOSE" SAFETY
- ④ 4 WIRE EDGE "CLOSE" SAFETY
- ⑤ N.C. SENSOR
- ▲ REMOVE JUMPER WHEN USED.
- Ⓐ WIRE IS NOT USED WHEN EXTERNAL INTERLOCK SWITCH OR STOP BUTTON IS USED.
- Ⓑ OBSTRUCTION SENSING DEVICES MAY BE N.O. TYPE (STANDARD AIR SWITCH, ELECTRIC EDGE, ETC.) OR N.C. "FAIL-SAFE" TYPE (PHOTOCELL, ETC.).
- Ⓒ MOVE RED WIRE FROM # 7 TO # 5 FOR MOMENTARY PRESSURE TO CLOSE.